

DHL Series — Belt Drive



DH-1502-LP2E1A (tank shown not included)

Designed to deliver powerful cleaning right where you need it, this industrial-duty, propane-powered, hot water pressure washer is a fully self-contained cart-mount unit. The reinforced powder coated frame makes it extremely durable.

Pump:

Belt drive triplex crankshaft AR pump with solid ceramic pistons

Motor:

Open drip-proof electric motor | 35-foot power cord with GFCI

Frame:

Reinforced powder coated cabinet-style steel frame | 10-inch flat-free tires

Components:

LP gas-fired (vapor only) natural draft with aspirating-type burner | High limit temperature control for added safety | LP gas regulator | Hour meter

Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F | Water output temperature is 250°F plus unit operates at 350-PSI in “wet” steam (DH-0703 model)

Unit Includes:

Quick connect nozzles - 0°, 15°, 25°, 40° and detergent nozzle | 50-foot x 3/8-inch steel wire-braided high pressure hose | 36-inch insulated lance | Professional-grade insulated trigger gun with safety lock-off



Portable LP

Hot Water – DHL Series – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PLUG TYPE	BTU per hour - LP GAS	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DH-0703-LP2E1A*	700	2.3	1.5 HP, 120V, 1Ø, 13.2A	NEMA 5-15P	200,000	57.5x35.5x59.5in.	471 lb.	348 lb.
DH-1502-LP2E1A	1500	1.8	2.0 HP, 120V, 1Ø, 18.8A	NEMA 5-20P	200,000	57.5x35.5x59.5in.	505 lb.	382 lb.

*Combination wet steam cleaner/pressure washer



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



DH-1502-LP2E1A

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.