

Hot Water Mini Trailer

Trailer-Mount 4000-PSI
Pressure Washer

Belt Drive — Gasoline



The compact design of the hot water mini trailer offers ease of transport without sacrificing powerful cleaning capabilities. This trailer package is engineered with a durable powder coated steel frame, a rear locking storage area and an industrial 4000-PSI belt-driven pressure washer with a 12V Beckett burner.



HMT-40004-0MGH shown with optional adjustable trailer coupler hitch, TX-0010



Hot Water Mini Trailer

Trailer-Mount 4000-PSI Pressure Washer – Belt Drive – Gasoline

Pump:

Adjustable stainless-steel and brass unloader valve | Forged brass manifold | Thermal relief valve

Engine:

Remote engine start and choke | 12V electric start – battery not included

Frame:

Reinforced powder coated steel frame | Locking rear storage area – 2.875 cubic feet | Sealed LED trailer lights | 2-inch ball hitch | Caster brake (Use when unhitched)

Components:

½-inch schedule 80 pipe coil with 4-pancake heat exchanger | 12V Beckett burner | No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel) | Engine and burner hour meters | 1,000-lb. axle

Miscellaneous:

Temperature rise 140°F/60°C above ambient

Safety Features:

Removable safety flag for transportation and guidance when backing up | Recommended maximum speed is 65 mph | DOT approved and National Association of Trailer Manufacturers (NATM) certified | 250°F high temperature safety limit switch

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° | 50-foot x ¾-inch steel wire-braided high pressure hose with quick connects | Professional-grade insulated trigger gun with safety lock-off | Adjustable pressure insulated dual lance

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAP.	BURNER FUEL CONS.	BTU PER HOUR	TIRES	DIMENSIONS (LxWxH)	GROSS VEHICLE WT.
HMT-4004-OMGH	4000	3.7	389cc Honda GX390 OHV	General	1.61 gallons	10.0 gallons	2.45 gph	343,000	(2) 4.80-8 8in. bias ply	99x43.5x36in.	1,000 lb.

Options:

PART NUMBER	DESCRIPTION
TX-0010	Adjustable trailer coupler hitch - Replaces the standard 2-inch ball hitch with a 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket
TX-0020	High pressure hose reel - 12-inch hose reel, 100-foot maximum hose length

Accessories:

PART NUMBER	DESCRIPTION
15-0160	75-foot x ¾-inch hose - 4500-PSI rated, R2, for use with hose reel, TX-0020
15-0161	100-foot x ¾-inch hose - 4500-PSI rated, R2, for use with hose reel, TX-0020
20-1366A52	Black powder coated rain cap - Protects boiler from moisture build-up when unit is left outside, octagonal
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents



Rear Storage Area

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov